

## ACYLINDERS

asphericon offers aspheric cylinders in plano-convex, plano-concave, bi-concave or bi-convex shapes and with both spherical and aspheric rear surfaces. Benefit from the following specifications of our customized and stocked acylinders.

Specifications	Custom Acylinder	StockOptics Acylinder
Size	Up to 200 mm × 96 mm	10 mm × 10 mm – 50 mm × 50 mm
RMS Irregularities (RMS <sub>r</sub> )	20 nm	≤ 500 nm
Surface Imperfections (Scratch/Dig)	20 - 10	60 - 40
Coating	Customer-specific	3 Standard coatings <sup>1</sup>
Laser Damage Threshold	Customer-specific	12 J/cm <sup>2</sup> , 100 Hz, 6 ns, 532 nm
Full-surface Interferometric Measurement	Optional	Optional
Materials	Customer-specific (almost every type of glass, silica, germanium, silicon, zerodur)	S-LAH64
Mounting	Customer-specific	-
RoHS & REACH Conformity		Certified

<sup>1</sup> A: R<sub>MAX</sub><1.0%, R<sub>AVG</sub>≤0.4%, 400-600 nm, AOI=0° | B: R<sub>MAX</sub><1.0%, R<sub>AVG</sub>≤0.4%, 600-1050 nm, AOI=0° | C: R<sub>MAX</sub><1.0%, R<sub>AVG</sub>≤0.4%, 1000-1600 nm, AOI=0°

asphericon GmbH  
Stockholmer Str. 9 | 07747 Jena  
Germany

+49 (0) 3641 - 3100 560  
+49 (0) 3641 - 3100 561

asphericon, Inc.  
8586 Potter Park Drive  
Sarasota, FL 34238 | USA

+1 - 941 - 564 0890

asphericon, s.r.o.  
Miliřská 449 | Jeřmanice 463 12  
Czech Republic

+420 488 100 300

sales@asphericon.com

www.asphericon.com